

# NCT-200 Non-Contact Tonometer





# Rex + Max = Rexxam

Rexxam, which means 'the king of the kings', is a respected and reliable brand.

Rexxam is a Japanese company with a celebrated 60 year history. With over 3,000 employees worldwide, Rexxam manufacture a wide range of products for various industries; from factory automation, automobiles and air conditioning systems, to beer and ski boots.

Since 1986, Rexxam has manufactured various high quality products for leading brands in the eye care industry, including SHIN-NIPPON. Rexxam had developed and manufactured products for SHIN-NIPPON since 1993 and in 2014 the company took over the SHIN-NIPPON brand.

We will be bringing high quality ophthalmic equipment to a global market. By combining precision engineering with industry leading innovation and experience in mass production, Rexxam produce unique products to support eye care specialists across the world.

Quality in vision care, we are Rexxam.



– 1960
Foundation of Rexxam

- 1986 Rexxam started the development and manufacturing of

ophthalmic devices as an OEM supplier 1993

Rexxam became the main OEM partner for SHIN-NIPPON

#### **SHIN-NIPPON**

2014 Rexxam acquired the SHIN-NIPPON brand SHIN-NIPPON by Rexxam

2018 The manufacturer brand Rexxam was inaugurated

Rexxam





# Compact & Ergonomic Design with Simple Opreration.

The air puff of Rexxam's Non-Contact Tonometer is gentle and quiet which minimises patient anxiety during measurement. Alignment is swift and easy to operate.

Through the pursuit of ergonomics and attention to detail combined with optimal material selection, Rexxam has achieved a compact design with superb operability and solid reliability.



#### Optimum monitor tilting and swivel angles

The monitor 30° left swivel allows user to assist patient position whilst operating the joystick. The 40° vertical tilt provides convenient operation in either a standing or sitting position.





# Smart Puff Control system (SPC)

The SPC system includes a newly developed algorithm measurement engine that instantly and precisely adjusts its air pressure to match patient intraocular pressure (IOP). Its quiet, soft air puff enhances patient comfort.



## Smart Alignment & Auto Shoot function

Smooth and accurate alignment function. Once aligned, automatic air puff measurement begins. Smooth and speedy operation that minimises patient anxiety.



### **IOP** Correction Function

The IOP value is automatically corrected (Corr.) by the input of the central corneal thickness measurement . The correction can be made either before or after measurement.





#### Triple safety system

The safety stopper prevents the nozzle from coming in contact with the patient's eye. Just in case the safety stopper is not properly locked in position, an alert "Beep" sound triggers and warning message "Too Close" appears on the monitor.





#### Capacitive touch sensor buttons

The capacitive touch sensor buttons work responsively whilst keeping the main screen clear from fingerprints, etc.



#### Intuitive joystick operation

The solid and ergonomic joystick ensures intuitive, comfortable and smooth operation.



#### Breath shield

A dedicated breath shield is available for hygiene or social distancing purposes. (Optional)



#### Reliability warning mark

The smart warning mechanism displays an asterisk (\*) on screen as well as on the printout, to indicate when the measured value has low reliability.





Intraocular Pressure(IOP) Measurement Range	1mmHg ~ 60mmHg / 0.1kPa ~ 8.0kPa	
Measurement Resolution	1mmHg / 0.1kPa	
Working Distance	11mm	
Target	Fixation Light : Green ( Blinking / Non-Blinking selectable )	
Start-up Method	Manual , Automatic	
IOP Correcction Function	With a corneal thickness input function	
Monitor	5.7 inch color LCD monitor	
Printer	Thermal line printer	
Power	Power Voltage	AC 100 - 240 V , 50/60Hz
	Power Consumption	60VA
	Sleep Mode	OFF , 3 , 5 , 10 min (selectable)
Data Output	RS-232C interface	
Size	Weight	approx. 13kg
	Dimensions	240mm(W) × 422mm(D) × 430mm(H)
Movement Range of The Measurement Unit	Forward - Backward : ±22mm Right - Left : ±43mm Up - Down : ±17mm	
Movement Range of The Chin Rest	Up - Down : ±30mm	
Movement Range of LCD	Swivel : left 30°	
	Vertical Tilt : up 40°	

#### Included Items

- Measuring Nozzle Cap
- Printer Roll Paper
- Chin Rest Paper
- Chin Rest Paper Pin
- Spare Fuse
- Dust Cover

Design and specifications are subject to change without prior notice.

#### Manufacturer



Rexxam Co.,Ltd. Kagawa factory 958 Ikeuchi, Konan-cho,

Takamatsu-shi, Kagawa-ken, 761-1494 Japan



Contact

Rexxam Co.,Ltd.

E-mail:eye@rexxam.co.jp

Website:https://www.rexxam.co.jp



Eye-care Instruments Sales Dept. Tokyo Office

2-4-2 Kandatsukasa-machi, Chiyoda-ku, Tokyo,

101-0048 Japan TEL:+81-3-6262-9471 FAX:+81-3-6262-9472

**Proudly** Made in Japan





Distributed by